




# ESTRELLA - SPIDER - BAGUE



NBR  
85°ShA




NBR  
85-90°ShA




Polyurethane  
93°ShA



Polyurethane  
93°ShA



Polyurethane  
98°ShA



Polyurethane  
64°ShD\*

## CARACTERÍSTICAS-CHARACTERISTICS-CARACTÉRISTIQUES

| TIPO TYPE                                                                                | NBR                                                              | NBR                                                                | POLIURETANO<br>POLYURETHANE | POLIURETANO<br>POLYURETHANE                                                         | POLIURETANO<br>POLYURETHANE                                                                  | POLIURETANO<br>POLYURETHANE                     |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------|--------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|-------------------------------------------------|
| USO<br>USE<br>UTILISATION                                                                | ALTA<br>ELASTICIDAD<br>HIGH<br>ELASTICITY<br>HAUTE<br>ELASTICITÉ | ALTA<br>TEMPERATURA<br>HIGH<br>TEMPERATURE<br>HAUTE<br>TEMPÉRATURE | ESTÁNDAR<br>STANDARD        | VULKOLLAN<br>MONTAJE<br>EXTERIOR<br>EXTERIOR<br>MOUNTING<br>EXTÉRIEUR DE<br>MONTAGE | VULKOLLAN<br>ALTA<br>TRANSMISION<br>DE PAR<br>HIGH<br>TRANSMISSION<br>TORQUE<br>HAUTE TORQUE | ALTA RIGIDEZ<br>HIGH RIGIDITY<br>HAUTE RIGIDITÉ |
| COLOR<br>COLOUR<br>COULEUR                                                               | NEGRO<br>BLACK<br>NOIR                                           | AZUL<br>BLUE<br>BLEU                                               | AMARILLA<br>YELLOW<br>JAUNE | ROJA<br>RED<br>ROUGE                                                                | VERDE<br>GREEN<br>VERT<br>BLANCA<br>WHITE<br>BLANC                                           | BLANCA<br>WHITE<br>BLANC                        |
| DUREZA<br>HARDNESS<br>DURETÉ                                                             | 85 °Sh A                                                         | 85 °/90°SH A                                                       | 93 °Sh A                    | 93 °Sh A                                                                            | 98 °Sh A                                                                                     | 64 °Sh D                                        |
| TEMPERATURA<br>TRABAJO /<br>WORKING<br>TEMPERATURE /<br>TEMPÉRATURE DE<br>FONCTIONNEMENT | - 20°C<br>+ 85°C                                                 | - 20°C<br>+135°C                                                   | - 20°C<br>+ 85°C            | - 20°C<br>+ 85°C                                                                    | - 20°C<br>+ 85°C                                                                             | - 20°C<br>+ 85°C                                |

| TIPO TYPE | PAR TRABAJO / WORKING TORQUE / TORQUE DE FONCTIONNEMENT |     |      |     |       |       |
|-----------|---------------------------------------------------------|-----|------|-----|-------|-------|
| 50X10     | -                                                       | 1,2 | 1,2  | 2   | 2     | 2,5   |
| 60X14     | -                                                       | 3,5 | 3,5  | 5   | 6     | 7,3   |
| 75X16     | 7,2                                                     | 8   | 8    | 12  | 13,6  | 16,8  |
| 75X23     | 11                                                      | -   | -    | -   | -     | -     |
| 90X20     | 14,4                                                    | 16  | 16   | 24  | 27,2  | 33,6  |
| 105X20    | 24,3                                                    | 27  | 27   | 40  | 45,9  | 56,7  |
| 120X20    | 36                                                      | 40  | 40   | 60  | 68    | 84    |
| 135X25    | 58,5                                                    | 65  | 65   | 90  | 110,5 | 136,5 |
| 150X28    | 81                                                      | 90  | 90   | 135 | 153   | 189   |
| 175X32    | 121,5                                                   | 135 | 135  | -   | 202,5 | 283,5 |
| 200X35    | 171                                                     | 190 | 190  | -   | 285   | 380   |
| 200X40    | -                                                       | 305 | 305  | -   | 381   | -     |
| 245X40    | -                                                       | -   | 489  | -   | 611   | -     |
| 300X50    | -                                                       | -   | 790  | -   | 1000  | -     |
| 350X55    | -                                                       | -   | 1200 | -   | 1500  | -     |
| 445x40    | -                                                       | -   | 2000 | -   | 2500  | -     |

ATEX



CERTIFICADO ATEX IM2 , IIGD2  
ATEX CERTIFICATES IM2 , IIGD2  
CERTIFICATS ATEX IM2 , IIGD2

LOS ACOPLAMIENTOS ALBERT ESTÁN CERTIFICADOS CONFORME A  
ALBERT COUPLING ARE CERTIFIED IN ACCORDANCE WITH  
LA ACCOUPLEMENTS ALBERT SONT CERTIFIÉS CONFORMES À  
FABRICACION DE ACOPLAMIENTOS ELÁSTICOS SIN SOLDADURA PARA TRANSMISIÓN DE POTENCIA

ISO 9001

BUREAU VERITAS  
Certification  
ESPMDO003187

